

* PRODUCT INFORMATION *

HUSKEY™ No.7 **LUBRICANT & SEALANT** **Gasoline & Solvent-Proof**

DESCRIPTION

HUSKEY No. 7 LUBRICANT & SEALANT is a blend of the finest synthetic lubricant base stocks, thickeners, and additives. **HUSKEY No. 7** is engineered for use in difficult-to-hold products while still providing a perfect seal.

USAGE

HUSKEY No. 7 LUBRICANT & SEALANT is designed for use in all lubricated valves in gasoline, LPG, natural gas, chlorinated solvents, aromatics, water, alcohols, and other service conditions where solvent action of product stream may cause valve operation problems.

ADVANTAGES

- 100% Synthetic
- Resistant to Practically All Solvents Including Chlorinated Hydrocarbons
- Will Not Contaminate Line Product
- Does Not Contain Clay Filters
- Leaves No Residue in Valves

TYPICAL SPECIFICATIONS

Color	Translucent White
Texture	Tacky-Smooth
Service Temperature	10EF to 425EF
Base Oils	Synthetic
Dropping Point	None

PACKAGE AVAILABILITY

5 qt. Can, 5 gal. Pail, and 15 gal. Keg
J & K gun size Sticks
Small Sticks for screw type lubricators

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the product for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

12/96



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE