

* PRODUCT INFORMATION *

HUSKEY™ No. 2 H.D. **PTFE SEALANT AND LUBRICANT**

DESCRIPTION

HUSKEY No.2 H.D. is a highly versatile valve sealant and lubricant that contains a balanced blend of fine to coarse PTFE particles suspended in a special synthetic lubricating carrier. **HUSKEY No.2 H.D.** is resistant to a large variety of line products such as water, crude or heating oils, fuels, dilute acids, steam, dilute caustics, petroleum solvents, butane, propane, L.P.G. odorants, etc.

USAGE AND APPLICATION

HUSKEY No.2 H.D. is designed for use on ball or plug valves that are leaking due to wear or scoring. It is excellent as a thread sealant for standard pipe or coarse threads, packing for stuffing boxes, and a supplementary sealant for valve stems.

HUSKEY No.2 H.D. is pumpable with a valve lubricant high pressure (10,000 psi) gun** such as the **HUSKEY 1010** Hand Gun or the **HUSKEY 1699** Hydraulic Hand Gun.

ADVANTAGES

- **Stop Leaks**
- **Will Not Dry Out**
- **Is Both A Sealant And Lubricant**
- **Broad Serviceability Range**

TYPICAL SPECIFICATIONS

| | |
|------------------------|-------------------------|
| Color | Reddish Brown |
| Texture | Viscous and Granular |
| Base Oil and Thickener | Synthetic |
| Bridging Agent | PTFE Fluorocarbon Resin |
| Service Range | 40EF to 500EF |
| Service Pressure | 15,000 PSI |

**Caution: Due to the multiple particle sizes of PTFE do not pump with air operated equipment. Not Recommended for Oxygen service.

PACKAGE AVAILABILITY

"J" Sticks (1¼ " x 8½) packaged 16 sticks/carton, 3 carton/case

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

1/05



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE